

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 13086 (1999): Pneumatic Fluid Power - Cylinders, 1 000 kPa (10 bar) Series - Rod End Spherical Eyes - Mounting Dimensions [PGD 16: Fluid Power]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



IS 13086 : 1999
ISO 8139 : 1991

(Reaffirmed 2004)

भारतीय मानक

वायवीय तरल शक्ति — सिलिंडर, 1 000 कि० पास्कल
(10 बार) शृंखला — छड़ सिरा गोलाकार
अक्ष — आरोपण आयाम
(पहला पुनरीक्षण)

Indian Standard

PNEUMATIC FLUID POWER — CYLINDERS, 1 000 kPa
(10 bar) SERIES — ROD END SPHERICAL EYES —
MOUNTING DIMENSIONS
(*First Revision*)

ICS 23.100.20

© BIS 1999

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

November 1999

Price Group 2

NATIONAL FOREWORD

This Indian Standard (First Revision) which is identical with ISO 8139 : 1991 'Pneumatic fluid power — Cylinders, 1 000 kPa (10 bar) series — Rod end spherical eyes — Mounting dimensions' issued by the International Organization for Standardization (ISO) was adopted by the Bureau of Indian Standards on the recommendation of the Pneumatic Fluid Power Systems Sectional Committee (PE 16) and approval of the Production Engineering Division Council.

This standard was first published in 1991 by adopting ISO 8139 : 1986. This ISO Standard has since been revised as ISO 8139 : 1991. In view of a number of changes observed in the revised ISO Standard, the Committee dealing with the subject decided to revise IS 13086 : 1991 by adopting the above ISO Standard as an Indian Standard.

In pneumatic fluid power systems, power is transmitted and controlled through a gas under pressure within a circuit. Pneumatic fluid power cylinder is one of the components of the above system. It converts power into linear mechanical force and motion. It consists of a movable element, that is, a piston and piston rod, operating within a cylindrical bore.

In the adopted standard, certain terminology, conventions and method of presentation are not identical to those used in Indian Standards. Attention is particularly drawn to the following:

- a) Wherever the words 'International Standard' appear, referring to this standard, they should be read as 'Indian Standard'.
- b) Comma (,) has been used as a decimal marker while in Indian Standards the current practice is to use a point (.) as the decimal marker.

In the adopted standard, reference appears to certain International Standards for which Indian Standards also exist. The corresponding Indian Standards which are to be substituted in their place are listed below along with their degree of equivalence for the editions indicated:

<i>International Standard</i>	<i>Corresponding Indian Standard</i>	<i>Degree of Equivalence</i>
ISO 286 - 2 : 1988 ISO system of limits and fits — Part 2 : Tables of standard tolerance grades and limit deviations for holes and shafts	IS 919 (Part 2) : 1993 ISO system of limits and fits : Part 2 Tables of standard tolerance grades and limit deviations for holes and shafts (<i>first revision</i>)	Technically Equivalent
ISO 5598 : 1985 Fluid power systems and components—Vocabulary	IS 10416 : 1992 Fluid power systems and components—Vocabulary (<i>first revision</i>)	Identical
ISO 6430 : 1992 Pneumatic fluid power — Single rod cylinders, with integral mountings — 1 000 kPa (10 bar) series, — Bores from 32 mm to 250 mm — Mounting dimensions	IS 12738 : 1995 Pneumatic fluid power — Single rod cylinders, 1 000 kPa (10 bar) series, with integral mountings, bores from 32 mm to 250 mm — Mounting dimensions (<i>first revision</i>)	do
ISO 6431 : 1992 Pneumatic fluid power — Single rod cylinders, with detachable mountings — 1 000 kPa (10 bar) series, — Bores from 32 mm to 320 mm — Mounting dimensions	IS 10143 : 1995 Pneumatic fluid power — Single rod cylinders, 1 000 kPa (10 bar) series, with detachable mountings, bores from 32 mm to 320 mm — Mounting dimensions (<i>first revision</i>)	do
IS 6432 : 1985 Pneumatic fluid power — Single rod cylinders — 10 bar (1 000 kPa) series — Bores from 8 mm to 25 mm — Mounting dimensions	IS 12723 : 1988 Pneumatic fluid power — Single rod cylinders, 1 000 kPa (10 bar) series — Bores from 8 mm to 25 mm — Mounting dimensions	do

(Continued on third cover)

Indian Standard

PNEUMATIC FLUID POWER — CYLINDERS, 1 000 kPa (10 bar) SERIES — ROD END SPHERICAL EYES — MOUNTING DIMENSIONS

(First Revision)

1 Scope

This International Standard specifies the mounting dimensions required for interchangeability of rod end spherical eyes of pneumatic cylinders. The rod end spherical eyes have been designed specifically for use with 1 000 kPa [10 bar¹⁾] series cylinders manufactured in accordance with ISO 6430, ISO 6431 and ISO 6432 but this does not limit their application.

The spherical bearing end eyes are used on piston rods of pneumatic cylinders for mechanically transmitting the cylinder force under oscillatory rotational and titling movements. The design of the rod end spherical eyes is based on the maximum forces resulting from the specified internal diameter of the cylinders and pressure according to ISO 6430, ISO 6431 and ISO 6432.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 286-2:1988, *ISO system of limits and fits — Part 2: Tables of standard tolerance grades and limit deviations for holes and shafts.*

ISO 5598:1985, *Fluid power systems and components — Vocabulary.*

ISO 6430:—²⁾, *Pneumatic fluid power — Single rod cylinders with integral mountings — 1 000 kPa (10 bar) series — Bores from 32 mm to 250 mm — Mounting dimensions.*

ISO 6431:—³⁾, *Pneumatic fluid power — Single rod cylinders with detachable mountings — 1 000 kPa (10 bar) series — Bores from 32 mm to 320 mm — Mounting dimensions.*

ISO 6432:1985, *Pneumatic fluid power — Single rod cylinders — 10 bar (1 000 kPa) series — Bores from 8 to 25 mm — Mounting dimensions.*

3 Definitions

For the purposes of this International Standard, the definitions given in ISO 5598 apply.

4 Mounting dimensions

See figure 1 and table 1.

1) 1 bar = 100 kPa = 10⁵ Pa; 1 Pa = 1 N/m².

2) To be published. (Revision of ISO 6430:1983)

3) To be published. (Revision of ISO 6431:1983)

As in the Original Standard, this Page is Intentionally Left Blank

As in the Original Standard, this Page is Intentionally Left Blank

Annex A **(informative)**

Bibliography

- [1] ISO 6099:1985, *Fluid power systems and components — Cylinders — Identification code for mounting dimensions and mounting types.*

(Continued from second cover)

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test, shall be rounded off in accordance with IS 2 : 1960 'Rules for rounding off numerical values (*revised*)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act, 1986* to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Review of Indian Standards

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Handbook' and 'Standards : Monthly Additions'.

This Indian Standard has been developed from Doc : No. PE 16 (0201).

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002
Telephones : 323 01 31, 323 94 02, 323 33 75

Telegrams: Manaksanstha
(Common to
all offices)

Regional Offices:

Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg
NEW DELHI 110002

Telephone

{ 323 76 17
323 38 41

Eastern : 1/14 C. I. T. Scheme VII M, V. I. P. Road, Maniktola
CALCUTTA 700054

{ 337 84 99, 337 85 61
337 86 26, 337 86 62

Northern : SCO 335-336, Sector 34-A, CHANDIGARH 160022

{ 60 38 43
60 20 25

Southern : C. I. T. Campus, IV Cross Road, CHENNAI 600113

{ 235 02 16, 235 04 42
235 15 19, 235 23 15

Western : Manakalaya, E9 MIDC, Marol, Andheri (East)
MUMBAI 400093

{ 832 92 95, 832 78 58
832 78 91, 832 78 92

Branches : AHMADABAD. BANGALORE. BHOPAL. BHUBANESHWAR.
COIMBATORE. FARIDABAD. GHAZIABAD. GUWAHATI. HYDERABAD. JAIPUR.
KANPUR. LUCKNOW. NAGPUR. PATNA. PUNE. THIRUVANANTHAPURAM.